

Title of the Paper

Steven J. Miller*

November 1, 2005

Mathematics Department
Brown University
Providence, RI 02912

Abstract

The point of these notes is to give a quick introduction to some of the standard commands of LaTeX; for more information see any reference book. Thus we concentrate on a few key things that will allow you to handle most situations. For the most part, we have tried to have the text describe the commands; though of course we cannot do this everywhere. You should view both the .tex code and the output (either .pdf or .dvi) simultaneously.

Contents

1	First Steps	2
1.1	General Mathematics	2
1.2	One Line Equations	4
1.3	Labelling Equations	5
1.4	Multi-Line Equations: Eqnarray	6
1.5	Lemmas, Propositions, Theorems and Corollaries	8
1.6	Using Subsubsections	9
1.6.1	Pythagoras	9
1.6.2	Garbage	10
1.6.3	New Pages	10
1.6.4	Prime Number Theorem	11
1.7	Matrices and Shortcuts	11

*E-mail: sjmill@math.brown.edu

2	Environments I	13
2.1	Shortcut Environments	13
2.2	Enumeration, Itemizing, and General Latex and Linux Commands	14
3	Graphics and Color	15
3.1	Inserting Graphics	15
3.2	Color	16
4	Environments II	16
4.1	Lists	16
4.2	Emphasize and Bolding	16
4.3	Centering Text	16
4.4	Referring to Bibliography	17
4.5	Font sizes	17
A	Psychohistorical Dynamics of the Sayshell Republic: An Analysis of the Rise of the Mule	18
B	Random Walks in High Dimensions: Choosing a Universe Interesting for Drunks	18

1 First Steps

LaTeX is a cross between a word processor and a programming language. The purpose is to allow one to write articles with lots of mathematical symbols and equations easily. The default is to be in non-mathematical mode; we discuss how to enter mathematical mode below. The first few lines of the code describe the formatting (font size is 12 for this, this is an article not a report or book, which packages we need (some are needed for including graphics, some for standard definitions of common symbols or expressions), short cut commands, how we want theorems, lemmas and the like to look, and so on). For now, you can keep these settings and just modify the text below.

1.1 General Mathematics

Garbage text for format purposes. Here is math mode: $\alpha^{\Gamma_3} + \beta_{\gamma}^{12}$. To enter math mode inside text, simply type a dollar sign. Type another dollar sign to exit math mode. Many of the symbols for everyday mathematics is as you would expect:

you start with a slash and then end with the command. Thus lowercase Greek letters are slash letter, such as slash alpha, slash beta, slash gamma: α , β , γ . Uppercase Greek letters (when they exist) are slash Gamma, slash Delta and so on: Γ , Δ . Sums, products and integrals are slash sum, slash prod and slash int: Σ , \prod , \int . Less than and equal to is slash le: \leq ; similarly greater than or equal to is slash ge: \geq . Being an element of is slash in: \in ; not an element of is slash not slash in: \notin . Subset is slash subset \subset , and so forth. Note many of these are exactly as you'd expect: $a \in A \subset B$ and $c \notin B$. Not equal to is slash neq and not divide is slash neq |: $4 \neq 5$ and $4 \nmid 5$.

Other common symbols like infinity are slash infity: ∞ , the section sign is slash S: \S , union is slash cup: \cup , and intersection is slash cap: \cap . To do math blackboard is slash mathbb { letter }; thus the integers and rationals are \mathbb{Z} and \mathbb{Q} . We can put arrows over things by slash overrightarrow { text }: \overrightarrow{v} . For the other direction it is overleftarrow, to underline it is overline, for a hat (like the Fourier transform) it is widehat: \widehat{f} . To have a square root it is slash sqrt { text }: $\sqrt{4x+1}$; if we want an nth root it is slash sqrt [n] { text }: $\sqrt[n]{4x+1}$.

Certain symbols (dollar signs, percent sign, pound sign, ambersand sign) are used in tex to mean other things: if we want these in texts we put a slash before them: $\$, \%, \#, \&, \{, \}, \backslash$. The slash backslash gives a back slash. For example, the percent sign is used for comments that you do not want the tex compiler to read; anything on the line with the percent is commented out and not displayed.

Many standard functions have shortcuts to make them look good: for example, $\backslash\cos, \backslash\sin, \backslash\tan, \backslash\log$ and so on: \cos, \sin, \tan, \log . Compare how things look with and without the \backslash : $\cos(\log(x)+1)$ versus $\cos(\log(x)+1)$; without the \backslash it italicizes. In fact, in math mode any text is automatically italicized. We discuss later how to handle text in math mode.

To do superscripts use a carot (shift-six) and to do subscripts use underscore (shift-minus sign). Thus x-squared is x^2 and integrating $f(x)$ from a to b is $\int_a^b f(x)dx$. If you have more than one character as the superscript or subscript, you must surround it by left and }s: compare x_{i+j}^2 to $x_i^2 + j$. Sometimes, to be safe, one surrounds both subscripts and superscripts with braces.

If there are frequently used expressions, it is worthwhile to define shortcuts. Instead of typing $\backslash\alpha$ to get an alpha, I can type $\backslash\ga$, because I have defined that to be a Greek alpha: α . Similarly for not divide it is $\backslash\ntdiv$ (as a shortcut for $\backslash\nmid$): $4 \nmid 5$ versus $4 \ntdiv 5$. The way we do shortcuts is earlier in the document, we do $\backslash\newcommand { \shortcut name } { command }$. Thus for example the shortcut for greek lowercase alpha is $\backslash\newcommand { \ga } { \alpha }$.

To do fractions, type `\frac { numerator } { denominator }`: $\frac{12}{34}$. If you have the ratio of two one-digit numbers, you do not need the braces: $\frac{1}{2}$; however, compare $\frac{1}{12}$ to $\frac{1}{1}2$. These are common errors in tex (forgetting braces; the same also happens often with exponents or subscripts); that is why often it is best to include the braces. Remember every `{` must be paired with a `}`.

There are many different text environments; for webpages a good one to do is `http://www.math.brown.edu/~sjmiller`. Notice when we do this that the tilde is not displayed; to have it display use `\sim`: thus we would write `http://www.math.brown.edu/~sjmiller`.

Some people might have latex environments where it will replace a α with the Greek letter alpha. Note that if you type α it might replace it with what a real alpha, while if I type α , the user defined shortcut, it does not replace.

1.2 One Line Equations

Here's how to do an equation. Once you type `\begin { equation }`, you've automatically entered math mode. Now if you type anything, say `\Lambda` or `\epsilon` or even some of our user-defined shortcuts, they will be properly formatted:

$$\frac{\Lambda'(s)}{\Lambda(s)} = s + \epsilon \int_a^b 3x^2 e^{2\pi ix} dx. \quad (1.1)$$

In the above, `frac` (with a `\` before it) gives a fraction; it puts the first thing in curly brackets as the numerator, and the second as the denominator. To do Greek letters, type `\letter` (for example, `\epsilon`), while an integral is `\int`, a sum is `\sum`, and so on.

I've made a shortcut for equations: `\be` for begin equation and `\ee` for end equation. It looks as follows

$$\frac{\Lambda'(s)}{\Lambda(s)} = \epsilon \int_a^b 3x^2 e^{2\pi ix} dx. \quad (1.2)$$

If you have a blank line between the text and the equation, it sometimes inserts space, and indents the next text as it is a new paragraph; if there is no blank line, it sometimes keeps them closer, and does not indent the following text.

For example, let us compare the following to the earlier examples (where we had blank lines). Thus we follow this text with

$$\frac{\Lambda'(s)}{\Lambda(s)} = s + \epsilon \int_a^b 3x^2 e^{2\pi ix} dx. \quad (1.3)$$

As there is no carriage return, this text is part of the same paragraph, and is thus not indented.

As long as we are discussing equations, let us consider the case when we have more involved expressions, for example, we might have

$$\left(\frac{\sin(x^2 + 3x)}{x} + \frac{4}{e^x}\right)^2. \quad (1.4)$$

Note how the left and right parentheses are too short. There are two ways to fix this. One way is to use `\Big (` (and `\Big)` (and `Bigg` if you need a bigger parentheses). A better way is to use `\left (` (and `\right)`); this automatically adjusts the size of the parentheses. Unlike the `Big` or `Bigg` commands, if you have a `\left` (you must match it with a `\right`). Thus

$$\left(\frac{\sin(x^2 + 3x)}{x} + \frac{4}{e^x}\right)^2. \quad (1.5)$$

1.3 Labelling Equations

What if I want to keep track of the equation number, so that I can refer to it in the text? For example, consider

$$\frac{\Lambda'(s)}{\Lambda(s)} = \epsilon \int_a^b 3x^2 e^{2\pi ix} dx. \quad (1.6)$$

The way we label an equation is, after the `\begin { equation }`, we write `\label { labelname }`.

Note the label. I can choose anything (as long as there are no numbers, just letters) for the name. I choose to label all equations with `eq` followed by a descriptive name; lemmas I start `lem` followed by a descriptive name, and so on.

To refer to the equation, I merely have to write `\ref { eqname }`; for example for the previous equation it would be `1.6`; however, it's better to write `Equation 1.6` or `(1.6)`. The difference between `\ref` and `\eqref` is that `\eqref` automatically puts parentheses around the equation number.

Whenever you add equations, you have to compile Latex twice to get the references correct. The advantage of using equation labels is that, if we add additional equations before the equation we want to refer to, the equation number of our equation changes; by using labels these are automatically updated.

For example, consider the following.

$$g(x) = \int_0^{\infty} f(x, y)dy. \tag{1.7}$$

We can refer to this and say by (1.7) of §1.3 we have.... You can label equations (or sections, theorems and so on) any way you want, though it is nice to have a standard method. I prefer to label equations by eq colon name, theorems by thm colon name, sections by sec colon name, sub-sections by subsec colon name, and so on.

1.4 Multi-Line Equations: Eqnarray

What if your equation is more than one line? You might want to use eqnarray instead of equation. The `\nonumber \\` is a carriage return without numbering that line; personally, I like to wait to the last line to number something. Here's an example:

$$\begin{aligned} \frac{\Lambda'(t)}{\Lambda(t+1)} &= f(x)g(s) + f(x-t) - g(s)f(x) \\ \frac{\Lambda'(t)}{\Lambda(t+1)} &= f(x-t) \end{aligned} \tag{1.8}$$

Again, if I don't want to type `begin eqnarray` I can use the shortcut (that I defined above):

$$\begin{aligned} \frac{\Lambda'(t)}{\Lambda(t+1)} &= f(x)g(s) + f(x-t) - g(s)f(x) \\ \frac{\Lambda'(t)}{\Lambda(t+1)} &= f(x-t) \end{aligned} \tag{1.9}$$

Here, I've chosen to use `bea` to stand for `begin equation array`. You can define your shortcuts almost freely (you can't use numbers in a shortcut definition).

The formatting is done by the ampersand signs, `&`. (Note: if you have a special symbol which you want to display in Latex, you put a `\` before it. Thus, to print a percent-sign in math mode is `%`, or to print a pound sign is `#`.) The `eqnarray` environment has two ampersands per line, and centers the lines on what is between the ampersands.

Usually, one does not repeat the left hand side. Thus, it is more natural to write

$$\begin{aligned}
\frac{\Lambda'(t)}{\Lambda(t+1)} &= f(x)g(s) + f(x-t) - g(s)f(x) \\
&= f(x-t)
\end{aligned} \tag{1.10}$$

Here's a somewhat lengthier example:

$$\begin{aligned}
\frac{1}{m} \sum_p^{m^\sigma} p^{-\frac{1}{2}} &\leq \frac{1}{m} \left(\sum_p^{m^\sigma} \frac{1}{p} \right)^{\frac{1}{2}} \left(\sum_p^{m^\sigma} 1 \right)^{\frac{1}{2}} \\
&\leq \frac{1}{m} (\log \log m^\sigma + A)^{\frac{1}{2}} (\text{Li}(x) + O(x^{\frac{1}{2}} \log x))^{\frac{1}{2}} \\
&\ll \frac{1}{m} (\log \log m)^{\frac{1}{2}} \left(\frac{2m^\sigma}{\log m} \right)^{\frac{1}{2}} \\
&\ll m^{\frac{1}{2}\sigma-1} \left(\frac{\log \log m}{\log m} \right)^{\frac{1}{2}}.
\end{aligned} \tag{1.11}$$

In the above, I have used a user defined command, `\foh`. That is a shortcut I've created to write $\frac{1}{2}$. If there is something you use many times, you should have a shortcut for it.

Note several things look wrong in the above equation. The parentheses are wrong-sized, and the mathematical function *Li* (the logarithmic integral

$$\text{Li}(x) = \int_2^x \frac{dt}{\log t}, \tag{1.12}$$

which estimates the number of primes at most x) is italicized. To remove the italization we write inside math mode `\rm text not to be italicized` :

$$\begin{aligned}
\frac{1}{m} \sum_p^{m^\sigma} p^{-\frac{1}{2}} &\leq \frac{1}{m} \left(\sum_p^{m^\sigma} \frac{1}{p} \right)^{\frac{1}{2}} \left(\sum_p^{m^\sigma} 1 \right)^{\frac{1}{2}} \\
&\leq \frac{1}{m} (\log \log m^\sigma + A)^{\frac{1}{2}} \left(\text{Li}(x) + O\left(x^{\frac{1}{2}} \log x\right) \right)^{\frac{1}{2}} \\
&\ll \frac{1}{m} (\log \log m)^{\frac{1}{2}} \left(\frac{2m^\sigma}{\log m} \right)^{\frac{1}{2}} \\
&\ll m^{\frac{1}{2}\sigma-1} \left(\frac{\log \log m}{\log m} \right)^{\frac{1}{2}}.
\end{aligned} \tag{1.13}$$

Finally, instead of `eqnarray` one often uses `align`:

$$\begin{aligned} f(x, y) &= (x + y)^3 \\ &= x^3 + 3x^2y + 3xy^2 + y^3. \end{aligned} \tag{1.14}$$

Note it spaces things slightly differently than `eqnarray`:

$$\begin{aligned} f(x, y) &= (x + y)^3 \\ &= x^3 + 3x^2y + 3xy^2 + y^3. \end{aligned} \tag{1.15}$$

If you want to use `align` and add additional spaces, one can do `\space`:

$$\begin{aligned} f(x, y) &= (x + y)^3 \\ &= x^3 + 3x^2y + 3xy^2 + y^3. \end{aligned} \tag{1.16}$$

1.5 Lemmas, Propositions, Theorems and Corollaries

Now let's add a lemma. Below is how one would write it. Notice all the English text is italicized. We'll follow the lemma immediately with a proposition. With the way our file is set up, we start a lemma with `\begin { lem }`, and end it with `\end { lem }`.

Lemma 1.1. *Let $\hat{\phi}(\xi) = \int_0^\infty \phi(x)e^{2\pi ix} dx$. Then $\hat{\phi}_r(\xi) = \frac{1}{r}\hat{\phi}(\xi/r)$.*

Proposition 1.2. *If $f \in C^3$ and $f'(0) = 0$, $f''(0) > 0$ then 0 is a local minimum.*

Proof. This follows immediately from the well known relation

$$3x + 2y = 4z, \tag{1.17}$$

which completes the proof. □

Notice the proof environment above. We start with `\begin { proof }`, follow it with the proof (which can contain equations), and then end with `\end proof`. The nice thing is this automatically italicizes the word `proof`, and ends with a box (which stands for QED, that which was to be shown, the symbol often used to indicate the end of the proof). It is important that the end proof be on the same line as the last text, or there will be extra spacing.

The following is a new lemma, and what is inside the `[]` gives the lemma a name.

Lemma 1.3 (Value of $\zeta(2)$). *Let $\zeta(s)$ denote the Riemann Zeta Function. Then*

$$\zeta(2) = \frac{\pi^2}{6}. \quad (1.18)$$

You can label lemmas just like you would equations:

Theorem 1.4. *[The Implicit Equation] Let $x, y, z \in \mathbb{C}$. Then*

$$x^y + y^z + z^x = -1 \quad (1.19)$$

If you view the file, you will notice that the name of the above is italicized. It is better to put the name first, then the label:

Theorem 1.5 (The Implicit Equation). *Let $x, y, z \in \mathbb{C}$. Then*

$$x^y + y^z + z^x = -1 \quad (1.20)$$

By Lemma 1.5, we see that the desired expression equals -1 . Note that you often have to compile twice before the labels are correct.

Corollary 1.6. *$x = y = z = 1$ is not a solution to the Implicit Equation from Theorem 1.4.*

Corollary 1.7 (Bob's Observation). *$x = y = -1, z = 1$ is a solution to the Implicit Equation from Theorem 1.4.*

Remark 1.8 (Seldon's Remark). *Here is how you do a remark; notice that the remark is italicized.*

1.6 Using Subsubsections

If we wanted, we could put subsubsections in a section. Again, `\section` is section, `\subsection` is a subsection, `\subsubsection` is a subsubsection; you then put the name between braces.

1.6.1 Pythagoras

If a subsection is very long, we might want to have sub-subsections in the subsections. The commands are exactly what you think.

Lemma 1.9 (Lengths of Sides). *The sum of the lengths of any two sides of a triangle are greater than the third length.*

1.6.2 Garbage

Here is another subsection.

Here is some more garbage text.

And here is some more.

Note the double `\above` forces a carriage return. More gobbledegook follows here, such as the quick brown fox and one bright day in the middle of the night.

If you start a paragraph with `\noindent` then there is no indentation.

1.6.3 New Pages

We are now going to force a new page. The next subsection will start on a new page. We do this by `\newpage`.

1.6.4 Prime Number Theorem

Below is the Prime Number Theorem. If we assume the Riemann Hypothesis we can take $\alpha = \frac{1}{2} + \epsilon$.

$$\pi(x) = \frac{x}{\log x} + O(x^\alpha) \quad (1.21)$$

1.7 Matrices and Shortcuts

If you have symbols you use many times, it is often convenient to define a shortcut. For example, I have defined `\foh` to be $\frac{1}{2}$ (stands for fraction: one half).

Let's do some more detailed examples. To do a 5×5 matrix type

$$A = \left(\begin{array}{ccccc} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \\ 16 & 17 & 18 & 19 & 20 \\ 16 & 17 & 188 & 19 & 20 \\ 121 & 122 & 123 & 124 & 125 \end{array} \right) \quad (1.22)$$

Some important points to note: the `\left` and the `\right` draw the left and right parentheses around the matrix, automatically adjusting to the proper size. Then we have a `\begin array`, followed by five `cs` in curly braces. This gives a 5×5 matrix, with each element centered. If instead of `cs` we used `ls`, it would left-justify (and `rs` would right justify). For example,

$$A = \left(\begin{array}{ccccc} 1 & 2 & 3 & 4 & 5 \\ 6 & 7 & 8 & 9 & 10 \\ 11 & 12 & 13 & 14 & 15 \\ 16 & 17 & 18 & 19 & 20 \\ 121 & 122 & 123 & 124 & 125 \end{array} \right) \quad (1.23)$$

Notice we use ampersand signs `&` between the various elements; this is similar to multi-line equations, where we used the ampersands to center things. We end each line with `\\`, which is a carriage return.

Latex allows you to define shortcuts that are functions of up to nine arguments with ease. Thus, I can have shortcut definitions for 2×2 and 3×3 matrices. To use my shortcuts (the newcommands at the top), one just types

$$A = \left(\begin{array}{cc} a & b \\ c & d \end{array} \right) \quad (1.24)$$

or

$$B = \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix}. \quad (1.25)$$

If you want determinants, you can do

$$\det(A) = \begin{vmatrix} a & b \\ c & d \end{vmatrix}, \quad \det(B) = \begin{vmatrix} a & b & c \\ d & e & f \\ g & h & i \end{vmatrix}. \quad (1.26)$$

Two remarks on the above equation. First, `\det` gives a nice determinant. For functions like `det`, `sin`, `cos`, if you don't put a `\` before them, Latex interprets them as text (letters). Thus, compare `det(A)`, `cos(A)`, `sin(A)`, `log(A)` to `det(A)`, `cos(A)`, `sin(A)`, `log(A)`.

Second, a `\` followed by a space gives a space. Latex ignores (for the most part) spaces. In the above, the `\space \space \space` gives three spaces (ie, helps format).

Finally, here are some other shortcuts I've created that you might find useful. Feel free to make your own!

Here is one to do a two case argument:

$$\Lambda(n) = \begin{cases} \log p & \text{if } p \text{ is a prime power} \\ 0 & \text{otherwise.} \end{cases} \quad (1.27)$$

Here is a way to do a three case argument.

$$\mu(n) = \begin{cases} 1 & \text{if } n = 1 \\ (-1)^r & \text{if } n \text{ is the product of } r \text{ distinct primes} \\ 0 & \text{if } n \text{ is divisible by the square of a prime.} \end{cases} \quad (1.28)$$

For the Legendre / Jacobi symbol with modulus p , simple use $\left(\frac{x}{p}\right)$.

The standard sets of numbers encountered are the natural numbers \mathbb{N} , the integers \mathbb{Z} , the reals \mathbb{R} , and the complex numbers \mathbb{C} .

If we want to do vectors, we just do \vec{v} ; set operations are $x \in A \cup B \cap C \subset D = G \oplus H$.

Sometimes we prefer to write

$$x = \bigcup_{i=1}^{\infty} A_i \text{ instead of } x \in \bigcup_{i=1}^{\infty} A_i. \quad (1.29)$$

Note the above has the text in emphasis mode. To avoid this, use either `mbox` or `text` (text is better):

$$x = \bigcup_{i=1}^{\infty} A_i \text{ instead of } x \in \bigcup_{i=1}^{\infty} A_i. \quad (1.30)$$

Here it is with `text` instead of `mbox`.

$$x = \bigcup_{i=1}^{\infty} A_i \text{ instead of } x \in \bigcup_{i=1}^{\infty} A_i. \quad (1.31)$$

Here it is using `remove emphasis \rm`:

$$x = \bigcup_{i=1}^{\infty} A_i \text{ insteadof } x \in \bigcup_{i=1}^{\infty} A_i. \quad (1.32)$$

Note with the `remove emphasis` that we have lost the space between `instead` and `of`; to add it back we would need a `\space`.

To do a unit vector, one can write $\hat{i}, \hat{j}, \hat{k}$. We also have $\prod_{i=1}^5 \sum_{j=1}^8 a_{ij}$.

We have now come to the end of the first section – it will automatically start the next section on a new page.

I like to put a lot of percent signs between sections (and a few carriage returns) to make editing easier.

2 Environments I

2.1 Shortcut Environments

To do an equation, recall we need `\begin curly brackets equation curly brackets`. Thus, we write

$$\sum_{n=1}^{\infty} \frac{1}{n^2} = \frac{\pi^2}{6} = \frac{8}{3} \left(\int_0^1 \frac{1}{1+x^2} dx \right)^2. \quad (2.1)$$

If you have a lot of equations or arrays of equations, you don't want to keep typing `begin equation` and `end equation`.

We've created some shortcuts: `\be` will be `begin equation`; `\ee` will end the equation; `bea` and `eea` will `begin` and `end` arrays of equations.

Thus,

$$\sum_{n=1}^{\infty} \frac{1}{n^2} = \frac{\pi^2}{6} = \frac{8}{3} \left(\int_0^1 \frac{1}{1+x^2} dx \right)^2 \quad (2.2)$$

does it as an equation, and

$$\begin{aligned} \sum_{n=1}^{\infty} \frac{1}{n^2} &= \frac{\pi^2}{6} \\ &= \frac{8}{3} \left(\int_0^1 \frac{1}{1+x^2} dx \right)^2 \end{aligned} \quad (2.3)$$

does it as an array of equations.

Other useful commands: `\textbf { text you want in bold }`: **this will put any text in bold**; `\emph { text you want emphasized }`: *this will emphasize or italicize text*; `\underline { text to underline }`: this will underline.

2.2 Enumeration, Itemizing, and General Latex and Linux Commands

We will use the shortcuts for the enumeration environment. First, the long form. We start with `\begin { enumerate }`. This starts the enumeration (ie, a list of items with each item numbered). Each item in the enumerated list starts with `\item`. To have sub-items we use `\subitem`; however, there are no bullet points or marks here; we can add a bullet with `\bullet`. We end with `\end { enumerate }`.

1. in whatever directory you want to latex, save the files `template.tex`, `yl.eps`.
This will give you a tex template with the image `yl.eps`.
 - Not the `\bullet` gives a bullet point.
2. The following commands work in many unix environments: at the unix prompt, move into the directory where you've saved the templates. To edit, type `emacs template.tex &` (the ampersand makes sure it opens in a new window). To compile is **Control-c-f**. Type `xdvi template.dvi &` to view your compiled file. If you make changes to the latex source file, just clicking on the `xdvi` file will (if you've compiled the latex file) automatically update the `dvi` file. `control-c` (let go of the two keys) ' displays error messages (it's on the same key as the tilde, don't hold down shift).

If instead of numbering we wanted bullets, we just change `enumerate` to `itemize`. Here `\subitem` also does not give bullet points. Instead of using bullets we could use diamonds, `\diamond`.

- To open a file for editing using emacs, type `emacs filename &`; the ampersand opens the file in a new window.
 - ◊ `Control-x-w` saves without exiting;
 - ◊ `Control-x-c` saves with exiting.
- General: We list some general commands:
 - ◊ `cd directory` changes the directory,
 - ◊ `ls` lists all files and sub-directories in current directory.

You can also use my shortcuts for these environments.

1. `ben` stands for begin `enumerate`.
2. `een` stands for end `enumerate`.
3. each line starts with `\item`.


`Itemize` is similar.

- `bi` is begin `itemize`.
- `ei` is end `itemize`.
- each line starts with `\item`.

3 Graphics and Color

3.1 Inserting Graphics

Let's end by inserting a picture (image courtesy of J. Ax and S. Kochen). The image extension should be `.eps`, and in the same directory as everything.



On some systems, if I try to view the .dvi file I have trouble seeing the picture; I need to convert it to a .ps file and then use ghostview or some such.

3.2 Color

If you have included the color package, you can write in color. Simply use the following:

This is to type in a shade of red. There are three parameters, red green blue, I think. Each is a number between 0 and 1. Note you start with a brace followed by rmfamily then the color specification, and you end with another brace like this.

If we type here, it is in black, the default color.

Now we are in a shade of blue. You can also use **bold test** in a color, as well as math notation, such as $a_i^j x_{ij} = \pi^e$, or whatever you want.

We can also switch colors to pure red or to pure blue or back to black in the middle of a paragraph.

4 Environments II

4.1 Lists

Enumerating lists:

1. This is the first item.
2. This is the second item.
3. This is the last item.

4.2 Emphasize and Bolding

If you use **this, then whatever is inside will be in bold**, while if you use *this, everything will be emphasized*, and this will cause the text to be underlined.

I have created a shortcut for textbf, namely **this will bold text as well**.

4.3 Centering Text

One can also center text:

Everything typed in here is centered.
Isn't centering wonderful?
I thought so too.

This is also wonderful.

The two slashes above give a extra carriage return. You can only have one double slash at the end of a line. If you want more, use bigskip.

4.4 Referring to Bibliography

The bibliography is included at the end. To refer to items, simply type [RSZ]. Note all the items in the bibliography have two abbreviations, one in brackets (which is what is displayed in the bibliography), and one in curly braces (the shortcut name); I often have the two the same..

Again, what is in brackets is what the computer will print; what is in curly braces is how you refer to it.

Thus, to refer to the book by Khinchin you should type \Kh: [Kh]. We can also refer to the appendices, such as see Appendix A or see §A.

4.5 Font sizes

We describe some different font sizes:

- This is huge.
- This is LARGE
- This is Large
- You guessed it.
- This is tiny.
- Back to normalsize.

Notice in the above how the bullet size changes; the reason is that we start off in normal size, but when we type `\huge` we enter huge mode; we are in huge mode until we type `\LARGE`, when we enter LARGE mode. Thus the bullet points are adjusted.

Consider the matrix $A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$. Boy does this look bad compiled. How about $A = \left(\begin{array}{cc} a & b \\ c & d \end{array} \right)$. This looks better.

Acknowledgements

Many of these shortcut commands are from a .tex template that Alex Barnett was kind enough to share with me.

A Psychohistorical Dynamics of the Sayshell Republic: An Analysis of the Rise of the Mule

This is the first appendix, works like you would expect.

B Random Walks in High Dimensions: Choosing a Universe Interesting for Drunks

This is the second appendix.

References

- [Da] H. Davenport, *Multiplicative Number Theory*, second edition, Graduate Texts in Mathematics **74**, Springer-Verlag, New York, 1980, revised by H. Montgomery.
- [Kh] A. Y. Khinchin, *Continued Fractions*, Third Edition, The University of Chicago Press, Chicago 1964.
- [RSZ] Z. Rudnick, P. Sarnak, and A. Zaharescu, *The Distribution of Spacings Between the Fractional Parts of $n^2\alpha$* , *Invent. Math.* **145** (2001), no. 1, 37–57.